

**MADE IN ITALY**



| FLOODED - FREE MAINTENANCE BATTERY |         |          |               |           |        |            |     |              |         |            |
|------------------------------------|---------|----------|---------------|-----------|--------|------------|-----|--------------|---------|------------|
| Code                               | Voltage | Capacity | Cold Cranking | Res. Cap. | Tester | Terminal   | Box | Bottom holds | Layout  | Per Pallet |
|                                    | V       | Ah 20h   | A (EN)        | Minutes   |        | Conical    |     |              |         |            |
| B013C                              | 12      | 75       | 640           | 120 (25A) | 680    | 1 standard | L3  | B13          | + right | 16x4=64    |

## TOP ENERGY EVO

| Classification EN50342-1 |    |    |    |
|--------------------------|----|----|----|
| W3                       | C2 | V3 | E1 |




### TECHNICAL CHARACTERISTICS




**BOX AND LID**  
PP



**FLAMES ARRESTOR**  
Placed in the Lid




**SULPHURIC ACID**  
Density  
1,29+/- 0,01g/ml  
Approximate volume 4,4 l



**TEMPERATURE**  
According to EN50342-1



**BATTERY WEIGHT**  
16,6 ±5% Kg



**PLATES**  
Expanded grids in  
Pb/Ca alloy